

I-LINE Plug-in Unit

Plug-in Unit with Schneider Electric MCCB (500A and below)

NSXF Breaker		Interrupting Current	Number of poles	Catalogue Number (3 poles breaker)	Trip Rating	Interrupting Current	Number of poles	Catalogue Number (3 poles breaker)
Trip Rating	kA (380/415V)	kA (380/415V)	poles	Side handle, without Vigi	A	kA (380/415V)	poles	Side handle, without Vigi
16	36	36	3, 4*	PNSXF34016GNS	100	36	3, 4*	PNSXF34100GNS
25	36	36	3, 4*	PNSXF34025GNS	125	36	3, 4*	PNSXF34125GNS
32	36	36	3, 4*	PNSXF34032GNS	160	36	3, 4*	PNSXF34160GNS
40	36	36	3, 4*	PNSXF34040GNS	200	36	3, 4*	PNSXF34200GNS
50	36	36	3, 4*	PNSXF34050GNS	250	36	3, 4*	PNSXF34250GNS
63	36	36	3, 4*	PNSXF34063GNS	400	36	3, 4*	PBNSXF34400GNS
80	36	36	3, 4*	PNSXF34080GNS	500	36	3, 4*	PBNSXF34500GNS
NSXN Breaker		Interrupting Current	Number of poles	Catalogue Number (3 poles breaker)	Trip Rating	Interrupting Current	Number of poles	Catalogue Number (3 poles breaker)
Trip Rating	kA (380/415V)	kA (380/415V)	poles	Side handle, without Vigi	A	kA (380/415V)	poles	Side handle, without Vigi
16	50	50	3, 4*	PNSXN34016GNS	100	50	3, 4*	PNSXN34100GNS
25	50	50	3, 4*	PNSXN34025GNS	125	50	3, 4*	PNSXN34125GNS
32	50	50	3, 4*	PNSXN34032GNS	160	50	3, 4*	PNSXN34160GNS
40	50	50	3, 4*	PNSXN34040GNS	200	50	3, 4*	PNSXN34200GNS
50	50	50	3, 4*	PNSXN34050GNS	250	50	3, 4*	PNSXN34250GNS
63	50	50	3, 4*	PNSXN34063GNS	400	50	3, 4*	PBNSXN34400GNS
80	50	50	3, 4*	PNSXN34080GNS	500	50	3, 4*	PBNSXN34500GNS
NSXH Breaker		Interrupting Current	Number of poles	Catalogue Number (3 poles breaker)	Trip Rating	Interrupting Current	Number of poles	Catalogue Number (3 poles breaker)
Trip Rating	kA (380/415V)	kA (380/415V)	poles	Side handle, without Vigi	A	kA (380/415V)	poles	Side handle, without Vigi
16	70	70	3, 4*	PNSXH34016GNS	100	70	3, 4*	PNSXH34100GNS
25	70	70	3, 4*	PNSXH34025GNS	125	70	3, 4*	PNSXH34125GNS
32	70	70	3, 4*	PNSXH34032GNS	160	70	3, 4*	PNSXH34160GNS
40	70	70	3, 4*	PNSXH34040GNS	200	70	3, 4*	PNSXH34200GNS
50	70	70	3, 4*	PNSXH34050GNS	250	70	3, 4*	PNSXH34250GNS
63	70	70	3, 4*	PNSXH34063GNS	400	70	3, 4*	PBNSXH34400GNS
80	70	70	3, 4*	PNSXH34080GNS	500	70	3, 4*	PBNSXH34500GNS
NSXS Breaker		Interrupting Current	Number of poles	Catalogue Number	Trip Rating	Interrupting Current	Number of poles	Catalogue Number
Trip Rating	kA (380/415V)	kA (380/415V)	poles	Side handle, without Vigi	A	kA (380/415V)	poles	Side handle, without Vigi
16	100	100	3, 4*	PNSXS34016GNS	100	100	3, 4*	PNSXS34100GNS
25	100	100	3, 4*	PNSXS34025GNS	125	100	3, 4*	PNSXS34125GNS
32	100	100	3, 4*	PNSXS34032GNS	160	100	3, 4*	PNSXS34160GNS
40	100	100	3, 4*	PNSXS34040GNS	200	100	3, 4*	PNSXS34200GNS
50	100	100	3, 4*	PNSXS34050GNS	250	100	3, 4*	PNSXS34250GNS
63	100	100	3, 4*	PNSXS34063GNS	400	100	3, 4*	PBNSXS34400GNS
80	100	100	3, 4*	PNSXS34080GNS	500	100	3, 4*	PBNSXS34500GNS

* Note: For 4 poles breaker plug-in unit, please replace the suffix GN with GT.

Plug-in Unit with Schneider Electric MCCB (above 500A)

NSN breaker		Interrupting Current	Number of poles	Catalogue Number (3 poles breaker)	Trip Rating	Interrupting Current	Number of poles	Catalogue Number (3 poles breaker)
Trip Rating	kA (380/415V)	kA (380/415V)	poles	Without Vigi, Horizontal installation	A	kA (380/415V)	poles	Without Vigi, Vertical installation
630	50	50	3, 4*	PTNSN34630GNH	100	100	3, 4*	PTNSN34630GNV
800	50	50	3, 4*	PTNSN34800GNH	125	100	3, 4*	PTNSN34800GNV
1000	50	50	3, 4*	PTNSN34100GNH	160	100	3, 4*	PTNSN34100GNV
NSH breaker		Interrupting Current	Number of poles	Catalogue Number (3 poles breaker)	Trip Rating	Interrupting Current	Number of poles	Catalogue Number (3 poles breaker)
Trip Rating	kA (380/415V)	kA (380/415V)	poles	Without Vigi, Horizontal installation	A	kA (380/415V)	poles	Without Vigi, Vertical installation
630	70	70	3, 4*	PTNSH34630GNH	100	100	3, 4*	PTNSH34630GNV
800	70	70	3, 4*	PTNSH34800GNH	125	100	3, 4*	PTNSH34800GNV
1000	70	70	3, 4*	PTNSH34100GNH	160	100	3, 4*	PTNSH34100GNV

* Note: For 4 poles breaker plug-in unit, please replace the suffix GN with GT.
For 3L+PE busway (3P3W), please replace the suffix GN with G.